




TECHNICAL SPECIFICATIONS | TRACK-MOUNTED SCREENING PLANT

# MOBISCREEN MS 15 Z





## TECHNICAL HIGHLIGHTS

- ▣ Double-deck screening unit
- ▣ Diesel-hydraulic drive
- ▣ Scalping screen
- ▣ Max. feed size: 400 mm

## TECHNICAL SPECIFICATIONS MS 15 Z

### Feeding unit

Feed capacity up to approx. (t/h)	400
Feed size max. (mm)	400
Feed height (mm)	3,580
Hopper capacity (m <sup>3</sup> )	8

### Belt conveyor feeder

Width x length (mm)	1,400 x 4,500
Type (optional)	variable speed

### Screening unit

Type	double-deck vibration screen
Top deck width x length (mm)	1,525 x 4,880
Bottom deck width x length (mm)	1,525 x 4,575

### Belt conveyor underflow material

Width x length (mm)	1,200 x 4,500
---------------------	---------------

### Bottom deck underflow discharge conveyor (fine fractions)

Width x length (mm)	900 x 7,600
Discharge height approx. (mm)	3,810

### Bottom deck overflow discharge conveyor (medium fractions)

Width x length (mm)	900 x 7,600
Discharge height approx. (mm)	3,360

### Top deck overflow discharge conveyor (oversize fractions)

Width x length (mm)	1,400 x 5,500
Discharge height approx. (mm)	3,600

### Drive

Drive concept	diesel-hydraulic
Powerpack CAT (Tier 3, 4f) (kW)	75

### Transport

Transport height approx. (mm)	3,395
Transport length approx. (mm)	15,330
Transport width approx. (mm)	2,900
Transport weight approx. (kg)	33,000