

Sandvik QA451 triple deck Doublescreen

Technical specification sheet



Building upon the highly advanced features of the QA440 and original QA450, the QA451 represents the second generation product with numerous product refinements, whilst retaining the triple deck screen box that enables it to produce up to four different product types plus one oversize.

Designed with maximum productivity, the QA451 incorporates a large feed hopper, two large screen boxes and extended conveyors that afford massive stockpiling capabilities.

The QA451 screenbox makes use of the tried and tested Doublescreen technology but with a unique triple deck design cementing Sandvik's position as a true world leader.

- Triple deck 6 x 1.5m (20' x 5') equivalent Doublescreen with four hydraulic folding product conveyors allowing four accurately sized products to be produced.
- Now with hydraulic folding oversize conveyor which features both hydraulic raise/lower and hydraulic slew functions eliminating the need for a crane on site and minimising relocation time between sites.

- New heavy duty feeder conveyor drive system for increased machine throughput.
- New oversize chutework has a 40% larger cross section area to eliminate bottle necks and material restrictions.
- Capable of working alongside large jaw crushers, yet precise enough to produce accurate aggregate products.
- Massive stockpiling capability through integrated hydraulic conveyors.
- Fully tracked for on-site mobility, easily transported between sites.
- Available with optional vibrating grid.
- Global aftermarket support, with standard stock parts to ensure minimum loss of production.
- Capable of operating in the most hostile environments.
- Machine designed for optimum fuel economy and low operating costs.

SANDVIK

Technical specifications

| | QA451 |
|---------------------------|---|
| Hopper | |
| Capacity | 7.5 m ³ / 9.8 yd ³ |
| Maximum capacity | 11.33 m ³ / 14.8 yd ³ |
| Type | Hydraulic Tipping Grid |
| Standard Aperture | 128mm / 5" |
| Feed conveyor belt | |
| Width | 1200mm / 3' 11" |
| Motor / G/Box Ratio | 125cc / R 23.6:1 |
| Belt Speed | 18 m/min |
| Screen | |
| Type | 2 off screenboxes, 2 Bearing 3 Deck |
| First screen box size | 3048 x 1524mm / 10' x 5' |
| Second screen box size | Top 3048 x 1524 mm / 10' x 5' Mid 3048 x 1524 mm / 10' x 5' Bottom 2439 x 1524 mm / 8' x 5' |
| Tensioning System | Manual Ratchet |
| Speed | 1200rpm |
| Throw | 7.7mm |
| Motor | 49cc x 2 off |
| Side Conveyors | Mid Overs RHS |
| Discharge Height | 5130mm / 16' 10" |
| Width | 700mm / 27.5" |
| Drive | Hydraulic Motor 395cc |
| Side Conveyors | Mid Fines LHS |
| Discharge Height | 4915mm / 16' 9" |
| Width | 700mm / 27.5" |
| Drive | Hydraulic Motor 395cc |
| Fines Conveyor | Fines |
| Discharge Height | 5030mm / 16' 6" |
| Width | 1200mm / 47" |
| Drive | Hydraulic Motor 395cc |

Options

Central auto lube
 Remote diesel pump
 Water pump (hydraulic) inc spray bars
 -20°C (-4°F) Arctic package
 -30°C (-22°F) Arctic package
 Wear resistant liners, hopper, feed boots and spreader plate
 13ft tipping grid and crusher feed box
 Crusher feed box to fit with vibrating grid
 Canvas covers and brackets only (all conveyors)

| | QA451 |
|-------------------------------|---------------------------|
| 4th Conveyor (O/Size) | Oversize LHS |
| Discharge Height | 4897mm / 16' 1" |
| Width | 650mm / 25.5" |
| Drive | Hydraulic Motor 395cc |
| Length | 9770mm / 32' 1" |
| Belt Speed | 90 m/min |
| Raise Lower Facility | Yes Hydraulic raise lower |
| Hydraulic Slew | Yes Hydraulic slew |
| Maximum Slew Angle | now 64° from hopper |
| Tracks | |
| Length | 3800mm / 12' 5" |
| Shoe Width | 500mm / 19.5" |
| Power Pack | |
| Engine Type | CAT C4.4 75kw / 100hp |
| Diesel Tank Size | 290 litres / 76.5 USG |
| Hydraulic Tank Size | 370 litres / 98 USG |
| General technical data | |
| Transport dimensions | |
| Length | 18370mm / 60' 3" |
| Width | 3200mm / 10' 6" |
| Height | 3550mm / 11' 8" |
| Operating dimensions | |
| Length | 18802mm / 61' 8" |
| Width | 17852mm / 58' 7" |
| Height | 6480mm / 21' 3" |
| Standard weight | 34,000 kg / 74,958 lbs |
| Performance | |
| Max feed size | 200mm / 8" |
| Capacity (up to) | 600MTPH / 661STPH |
| Travel speed | 1.06K/H / 0.66MPH |

Note. All weights and dimensions are for standard units only

Dust suppression spraybars complete with hosing
 Pull cords on the fines, midgrade, oversize and fourth conveyor
 Tail conveyor canvas covers
 Double deck vibrating grid
 Screening media
 Lighting masts
 Overband magnet and frame
 Vibrating grid wing extensions

The units depicted show all options currently available, and the colour scheme reflects the eventual scheme to be used. Current models may differ from those featured in this brochure. Please contact Sandvik to clarify specification and options. The material in this brochure is of general application for information and guidance only, and no representation or warranty is made or given by the manufacturer that its products will be suitable for a customer's particular purpose and enquiry should always be made of the manufacturer to ensure such suitability. Whilst reasonable efforts have been made in the preparation of this document to ensure its accuracy, the manufacturer assumes no liability resulting from errors or omissions in this document, or from the use or interpretation of the information contained herein. The manufacturer reserves the right to make changes to the information in this brochure and the product design without reservation and without notification to users.

SANDVIK CONSTRUCTION MOBILE CRUSHERS AND SCREENS LTD
 HEARTHCOKE ROAD SWADLINCOTE DERBYSHIRE DE11 9DU ENGLAND
 TEL +44 (0)1283 212121 FAX +44 (0) 1283 217342 info.mobilecs@sandvik.com www.construction.sandvik.com

